



The ARM Instruction Set

ARM Technical Documents

- * **ARM Corporation**

- <http://www.arm.com>

- * **Technical reference manuals**

- ARM7TDMI Rev4, ARM9TDMI Rev3, ARM720T Rev3
 - ARM & Thumb instruction set quick reference card
 - Introduction to the Thumb extension to the ARM architecture

- * **Application notes**

- * **Technical specifications**

- ARM-Thumb procedure call standard
 - AMBA specification

- * **User guides**

- ARM Evaluator-7T board user guide
 - Target development system user guide

Processor Modes

* **The ARM has six operating modes:**

- *User* (unprivileged mode under which most tasks run)
- *FIQ* (entered when a high priority (fast) interrupt is raised)
- *IRQ* (entered when a low priority (normal) interrupt is raised)
- *Supervisor* (entered on reset and when a Software Interrupt instruction is executed)
- *Abort* (used to handle memory access violations)
- *Undef* (used to handle undefined instructions)

* **ARM Architecture Version 4 adds a seventh mode:**

- *System* (privileged mode using the same registers as user mode)

The Registers

- * **ARM has 37 registers in total, all of which are 32-bits long.**
 - 1 dedicated program counter
 - 1 dedicated current program status register
 - 5 dedicated saved program status registers
 - 30 general purpose registers
- * **However these are arranged into several banks, with the accessible bank being governed by the processor mode. Each mode can access**
 - a particular set of r0-r12 registers
 - a particular r13 (the stack pointer) and r14 (link register)
 - r15 (the program counter)
 - cpsr (the current program status register)**and privileged modes can also access**
 - a particular spsr (saved program status register)

Register Organisation


General registers and Program Counter

User32 / System	FIQ32	Supervisor32	Abort32	IRQ32	Undefined32
r0	r0	r0	r0	r0	r0
r1	r1	r1	r1	r1	r1
r2	r2	r2	r2	r2	r2
r3	r3	r3	r3	r3	r3
r4	r4	r4	r4	r4	r4
r5	r5	r5	r5	r5	r5
r6	r6	r6	r6	r6	r6
r7	r7	r7	r7	r7	r7
r8	r8_fiq	r8	r8	r8	r8
r9	r9_fiq	r9	r9	r9	r9
r10	r10_fiq	r10	r10	r10	r10
r11	r11_fiq	r11	r11	r11	r11
r12	r12_fiq	r12	r12	r12	r12
r13 (sp)	r13_fiq	r13_svc	r13_abt	r13_irq	r13_undef
r14 (lr)	r14_fiq	r14_svc	r14_abt	r14_irq	r14_undef
r15 (pc)	r15 (pc)	r15 (pc)	r15 (pc)	r15 (pc)	r15 (pc)

Program Status Registers

cpsr	cpsr	cpsr	cpsr	cpsr	cpsr
	spsr_fiq	spsr_svc	spsr_abt	spsr_irq	spsr_undef


Register Example: User to FIQ Mode



Accessing Registers using ARM Instructions

- * **No breakdown of currently accessible registers.**
 - All instructions can access r0-r14 directly.
 - Most instructions also allow use of the PC.
- * **Specific instructions to allow access to CPSR and SPSR.**
- * **Note : When in a privileged mode, it is also possible to load / store the (banked out) user mode registers to or from memory.**
 - See later for details.

The Program Status Registers (CPSR and SPSRs)



Copies of the ALU status flags (latched if the instruction has the "S" bit set).

- * **Condition Code Flags**

N = **N**egative result from ALU flag.

Z = **Z**ero result from ALU flag.

C = ALU operation **C**arried out

V = ALU operation o**V**erflowed

- * **Mode Bits**

M[4:0] define the processor mode.

- * **Interrupt Disable bits.**

I = 1, disables the IRQ.

F = 1, disables the FIQ.

- * **T Bit (Architecture v4T only)**

T = 0, Processor in ARM state

T = 1, Processor in Thumb state

Condition Flags

	Logical Instruction	Arithmetic Instruction
<u>Flag</u>		
Negative (N='1')	No meaning	Bit 31 of the result has been set Indicates a negative number in signed operations
Zero (Z='1')	Result is all zeroes	Result of operation was zero
Carry (C='1')	After Shift operation '1' was left in carry flag	Result was greater than 32 bits
oVerflow (V='1')	No meaning	Result was greater than 31 bits Indicates a possible corruption of the sign bit in signed numbers

The Program Counter (R15)

- * **When the processor is executing in ARM state:**
 - All instructions are 32 bits in length
 - All instructions must be word aligned
 - Therefore the PC value is stored in bits [31:2] with bits [1:0] equal to zero (as instruction cannot be halfword or byte aligned).
 - * **R14 is used as the subroutine link register (LR) and stores the return address when Branch with Link operations are performed, calculated from the PC.**
 - * **Thus to return from a linked branch**
 - `MOV r15, r14`
- or**
- `MOV pc, lr`

Exception Handling and the Vector Table

* **When an exception occurs, the core:**

- Copies CPSR into SPSR_<mode>
- Sets appropriate CPSR bits
 - ◆ If core implements ARM Architecture 4T and is currently in Thumb state, then
 - ARM state is entered.
 - ◆ Mode field bits
 - ◆ Interrupt disable flags if appropriate.
- Maps in appropriate banked registers
- Stores the “*return address*” in LR_<mode>
- Sets PC to vector address


* **To return, exception handler needs to:**

- Restore CPSR from SPSR_<mode>
- Restore PC from LR_<mode>

0x00000000	Reset
0x00000004	Undefined Instruction
0x00000008	Software Interrupt
0x0000000C	Prefetch Abort
0x00000010	Data Abort
0x00000014	Reserved
0x00000018	IRQ
0x0000001C	FIQ

The Instruction Pipeline

- * **The ARM uses a pipeline in order to increase the speed of the flow of instructions to the processor.**
 - Allows several operations to be undertaken simultaneously, rather than serially.



- * **Rather than pointing to the instruction being executed, the PC points to the instruction being fetched.**

Quiz #1 - Verbal

- * **What registers are used to store the program counter and link register?**
- * **What is r13 often used to store?**
- * **Which mode, or modes has the fewest available number of registers available? How many and why?**


ARM Instruction Set Format

31	2827	1615	87	0	Instruction type					
Cond	0 0 I	Opcode	S	Rn	Rd	Operand2				Data processing / PSR Transfer
Cond	0 0 0 0 0 0	A S	Rd	Rn	Rs	1 0 0 1	Rm			Multiply
Cond	0 0 0 0 1	U A S	RdHi	RdLo	Rs	1 0 0 1	Rm			Long Multiply (v3M / v4 only)
Cond	0 0 0 1 0	B 0 0	Rn	Rd	0 0 0 0	1 0 0 1	Rm			Swap
Cond	0 1 I	P U B W L	Rn	Rd	Offset					Load/Store Byte/Word
Cond	1 0 0	P U S W L	Rn	Register List						Load/Store Multiple
Cond	0 0 0	P U 1 W L	Rn	Rd	Offset1	1 S H 1	Offset2			Halfword transfer : Immediate offset (v4 only)
Cond	0 0 0	P U 0 W L	Rn	Rd	0 0 0 0	1 S H 1	Rm			Halfword transfer: Register offset (v4 only)
Cond	1 0 1	L	Offset							Branch
Cond	0 0 0 1	0 0 1 0	1 1 1 1	1 1 1 1	1 1 1 1	0 0 0 1	Rn			Branch Exchange (v4T only)
Cond	1 1 0	P U N W L	Rn	CRd	CPNum	Offset				Coprocessor data transfer
Cond	1 1 1 0	Op1		CRn	CRd	CPNum	Op2	0	CRm	Coprocessor data operation
Cond	1 1 1 0	Op1	L	CRn	Rd	CPNum	Op2	1	CRm	Coprocessor register transfer
Cond	1 1 1 1	SWI Number								Software interrupt

Conditional Execution

- * **Most instruction sets only allow branches to be executed conditionally.**
- * **However by reusing the condition evaluation hardware, ARM effectively increases number of instructions.**
 - All instructions contain a condition field which determines whether the CPU will execute them.
 - Non-executed instructions soak up 1 cycle.
 - Still have to complete cycle so as to allow fetching and decoding of following instructions.
- * **This removes the need for many branches, which stall the pipeline (3 cycles to refill).**
 - Allows very dense in-line code, without branches.
 - The Time penalty of not executing several conditional instructions is frequently less than overhead of the branch or subroutine call that would otherwise be needed.

The Condition Field





Using and updating the Condition Field

- * **To execute an instruction conditionally, simply postfix it with the appropriate condition:**
 - For example an add instruction takes the form:
 - `ADD r0,r1,r2` ; `r0 = r1 + r2` (ADDAL)
 - To execute this only if the zero flag is set:
 - `ADDEQ r0,r1,r2` ; If zero flag set then...
 - ; ... `r0 = r1 + r2`
- * **By default, data processing operations do not affect the condition flags (apart from the comparisons where this is the only effect). To cause the condition flags to be updated, the S bit of the instruction needs to be set by postfixing the instruction (and any condition code) with an “S”.**
 - For example to add two numbers and set the condition flags:
 - `ADDS r0,r1,r2` ; `r0 = r1 + r2`
 - ; ... and set flags

Conditional Execution cont.

- * Check the conditional field of CPSR and the conditional field of current instruction.
 - If the condition matches, current instruction is executed; otherwise, current instruction execution is aborted.



Conditional Execution cont.


* Reducing the number of branches

- MOVS r0, r1, LSR #1 ; C(flag) := r1[0]
- MOVCC r0, #10 ; if C=0, then r0 := 10
- MOVCS r0, #11 ; if C=1, then r0 := 11

- MOVS r0, r4 ; if r4==0 then r0 := 0
- MOVNE r0, #1 ; else r0 := 1

Branch instructions (1)

- * **Branch :** $B\{\text{<cond>}\} \text{ label}$
- * **Branch with Link :** $BL\{\text{<cond>}\} \text{ sub_routine_label}$




- * **The offset for branch instructions is calculated by the assembler:**
 - By taking the difference between the branch instruction and the target address minus 8 (to allow for the pipeline).
 - This gives a 26 bit offset which is right shifted 2 bits (as the bottom two bits are always zero as instructions are word – aligned) and stored into the instruction encoding.
 - This gives a range of ± 32 Mbytes.

Branch instructions (2)

- * **When executing the instruction, the processor:**
 - shifts the offset left two bits, sign extends it to 32 bits, and adds it to PC.
- * **Execution then continues from the new PC, once the pipeline has been refilled.**
- * **The "Branch with link" instruction implements a subroutine call by writing PC-4 into the LR of the current bank.**
 - i.e. the address of the next instruction following the branch with link (allowing for the pipeline).
- * **To return from subroutine, simply need to restore the PC from the LR:**
 - `MOV pc, lr`
 - Again, pipeline has to refill before execution continues.
- * **The "Branch" instruction does not affect LR.**
- * **Note: Architecture 4T offers a further ARM branch instruction, BX**
 - See Thumb Instruction Set Module for details.

Data processing Instruction Format



Data processing Instructions

- * **Largest family of ARM instructions, all sharing the same instruction format.**
- * **Contains:**
 - Arithmetic operations
 - Comparisons (no results - just set condition codes)
 - Logical operations
 - Data movement between registers
- * **Remember, this is a load / store architecture**
 - These instruction only work on registers, ***NOT*** memory.
- * **They each perform a specific operation on one or two operands.**
 - First operand always a register - Rn
 - Second operand sent to the ALU via barrel shifter.
- * **We will examine the barrel shifter shortly.**

Arithmetic Operations

* Operations are:

- ADD operand1 + operand2
- ADC operand1 + operand2 + carry
- SUB operand1 - operand2
- SBC operand1 - operand2 + carry - 1
- RSB operand2 - operand1
- RSC operand2 - operand1 + carry - 1

* Syntax:

- <Operation>{<cond>}{S} Rd, Rn, Operand2

* Examples

- ADD r0, r1, r2
- SUBGT r3, r3, #1
- RSBLES r4, r5, #5

Comparisons

- * **The only effect of the comparisons is to**
 - **UPDATE THE CONDITION FLAGS.** Thus no need to set S bit.
- * **Operations are:**
 - CMP operand1 - operand2, but result not written
 - CMN operand1 + operand2, but result not written
 - TST operand1 AND operand2, but result not written
 - TEQ operand1 EOR operand2, but result not written
- * **Syntax:**
 - <Operation>{<cond>} Rn, Operand2
- * **Examples:**
 - CMP r0, r1
 - TSTEQ r2, #5

Logical Operations

* Operations are:

- AND operand1 AND operand2
- EOR operand1 EOR operand2
- ORR operand1 OR operand2
- BIC operand1 AND NOT operand2 [ie bit clear]

* Syntax:

- <Operation>{<cond>}{S} Rd, Rn, Operand2

* Examples:

- AND r0, r1, r2
- BICEQ r2, r3, #7
- EORS r1,r3,r0

Data Movement

* **Operations are:**

- MOV operand2
- MVN NOT operand2

Note that these make no use of operand1.


* **Syntax:**

- <Operation>{<cond>}{S} Rd, Operand2

* **Examples:**

- MOV r0, r1
- MOVS r2, #10
- MVNEQ r1, #0

Quiz #2



* **Convert the GCD algorithm given in this flowchart into**

- 1) “Normal” assembler, where only branches can be conditional.
- 2) ARM assembler, where all instructions are conditional, thus improving code density.

* **The only instructions you need are CMP, B and SUB.**

Quiz #2 - Sample Solutions

“Normal” Assembler

```
gcd    cmp r0, r1      ;reached the end?
        beq stop
        blt less       ;if r0 > r1
        sub r0, r0, r1  ;subtract r1 from r0
        bal gcd
less   sub r1, r1, r0   ;subtract r0 from r1
        bal gcd
stop
```

ARM Conditional Assembler

```
gcd    cmp    r0, r1      ;if r0 > r1
        subgt r0, r0, r1  ;subtract r1 from r0
        sublt r1, r1, r0  ;else subtract r0 from r1
        bne   gcd        ;reached the end?
```

The Barrel Shifter

- * **The ARM doesn't have actual shift instructions.**
- * **Instead it has a barrel shifter which provides a mechanism to carry out shifts as part of other instructions.**
- * **So what operations does the barrel shifter support?**

Barrel Shifter - Left Shift

- * Shifts left by the specified amount (multiplies by powers of two) e.g.
LSL #5 = multiply by 32

Logical Shift Left (LSL)



Barrel Shifter - Right Shifts

Logical Shift Right

- Shifts right by the specified amount (divides by powers of two) e.g.


LSR #5 = divide by 32



Arithmetic Shift Right

- Shifts right (divides by powers of two) and preserves the sign bit, for 2's complement operations. e.g.

ASR #5 = divide by 32




Barrel Shifter - Rotations

Rotate Right (ROR)

- Similar to an ASR but the bits wrap around as they leave the LSB and appear as the MSB.


e.g. ROR #5

- Note the last bit rotated is also used as the Carry Out.




Rotate Right Extended (RRX)


- This operation uses the CPSR C flag as a 33rd bit.
- Rotates right by 1 bit. Encoded as ROR #0.



The cross-bar switch barrel shifter principle



Using the Barrel Shifter: The Second Operand



* **Register, optionally with shift operation applied.**

* **Shift value can be either:**

- 5 bit unsigned integer
- Specified in bottom byte of another register.


* **Immediate value**

- 8 bit number
- Can be rotated right through an even number of positions.
- Assembler will calculate rotate for you from constant.

Second Operand : Shifted Register

- * **The amount by which the register is to be shifted is contained in either:**
 - the immediate 5-bit field in the instruction
 - *NO OVERHEAD*
 - Shift is done for free - executes in single cycle.
 - the bottom byte of a register (not PC)
 - Then takes extra cycle to execute
 - ARM doesn't have enough read ports to read 3 registers at once.
 - Then same as on other processors where shift is separate instruction.
- * **If no shift is specified then a default shift is applied: LSL #0**
 - i.e. barrel shifter has no effect on value in register.

Shift Format



Second Operand : Using a Shifted Register

- * Using a multiplication instruction to multiply by a constant means first loading the constant into a register and then waiting a number of internal cycles for the instruction to complete.
- * A more optimum solution can often be found by using some combination of MOVs, ADDs, SUBs and RSBs with shifts.
 - Multiplications by a constant equal to a $((\text{power of } 2) \pm 1)$ can be done in one cycle.
- * **Example: $r0 = r1 * 5$**
$$= r1 + (r1 * 4)$$
$$\Leftrightarrow \text{ADD } r0, r1, r1, \text{LSL } \#2$$
- * **Example: $r2 = r3 * 105$**
$$= r3 * 15 * 7$$
$$= r3 * (16 - 1) * (8 - 1)$$
$$\Leftrightarrow \text{RSB } r2, r3, r3, \text{LSL } \#4 \quad ; r2 = r3 * 15$$
$$\Leftrightarrow \text{RSB } r2, r2, r2, \text{LSL } \#3 \quad ; r2 = r2 * 7$$

Second Operand : Immediate Value (1)

- * **There is no single instruction which will load a 32 bit immediate constant into a register without performing a data load from memory.**
 - All ARM instructions are 32 bits long
 - ARM instructions do not use the instruction stream as data.
- * **The data processing instruction format has 12 bits available for operand2**
 - If used directly this would only give a range of 4096.
- * **Instead it is used to store 8 bit constants, giving a range of 0 - 255.**
- * **These 8 bits can then be rotated right through an even number of positions (ie RORs by 0, 2, 4,..30).**
 - This gives a much larger range of constants that can be directly loaded, though some constants will still need to be loaded from memory.

Second Operand : Immediate Value (2)

*** This gives us:**

- 0 - 255 [0 - 0xff]
- 256,260,264,...,1020 [0x100-0x3fc, step 4, 0x40-0xff ror 30]
- 1024,1040,1056,...,4080 [0x400-0xff0, step 16, 0x40-0xff ror 28]
- 4096,4160, 4224,...,16320 [0x1000-0x3fc0, step 64, 0x40-0xff ror 26]

*** These can be loaded using, for example:**

- MOV r0, #0x40, 26 ; => MOV r0, #0x1000 (ie 4096)

*** To make this easier, the assembler will convert to this form for us if simply given the required constant:**

- MOV r0, #4096 ; => MOV r0, #0x1000 (ie 0x40 ror 26)

*** The bitwise complements can also be formed using MVN:**

- MOV r0, #0xFFFFFFFF ; assembles to MVN r0, #0

*** If the required constant cannot be generated, an error will be reported.**

Loading full 32 bit constants

- * **Although the MOV/MVN mechanism will load a large range of constants into a register, sometimes this mechanism will not generate the required constant.**
- * **Therefore, the assembler also provides a method which will load *ANY* 32 bit constant:**
 - `LDR rd,=numeric constant`
- * **If the constant can be constructed using either a MOV or MVN then this will be the instruction actually generated.**
- * **Otherwise, the assembler will produce an LDR instruction with a PC-relative address to read the constant from a literal pool.**
 - `LDR r0,=0x42` ; generates `MOV r0,#0x42`
 - `LDR r0,=0x55555555` ; generate `LDR r0,[pc, offset to lit pool]`
- * **As this mechanism will always generate the best instruction for a given case, it is the recommended way of loading constants.**

Multiplication Instructions

- * **The Basic ARM provides two multiplication instructions.**
 - * **Multiply**
 - $\text{MUL}\{\text{<cond>}\}\{\text{S}\} \text{ Rd, Rm, Rs} \quad ; \text{ Rd} = \text{Rm} * \text{Rs}$
 - * **Multiply Accumulate - does addition for free**
 - $\text{MLA}\{\text{<cond>}\}\{\text{S}\} \text{ Rd, Rm, Rs, Rn} \quad ; \text{ Rd} = (\text{Rm} * \text{Rs}) + \text{Rn}$
 - * **Restrictions on use:**
 - Rd and Rm cannot be the same register
 - Can be avoided by swapping Rm and Rs around. This works because multiplication is commutative.
 - Cannot use PC.
- These will be picked up by the assembler if overlooked.**
- * **Operands can be considered signed or unsigned**
 - Up to user to interpret correctly.

Quiz #3

1. Specify instructions which will implement the following:

a) $r0 = 16$

b) $r1 = r0 * 4$

c) $r0 = r1 / 16$ ($r1$ signed 2's comp.)

d) $r1 = r2 * 7$

2. What will the following instructions do?

a) ADDS r0, r1, r1, LSL #2

b) RSB r2, r1, #0

3. What does the following instruction sequence do?

ADD r0, r1, r1, LSL #1

SUB r0, r0, r1, LSL #4

ADD r0, r0, r1, LSL #7


Load / Store Instructions

- * **The ARM is a Load / Store Architecture:**
 - Does not support memory to memory data processing operations.
 - Must move data values into registers before using them.
- * **This might sound inefficient, but in practice isn't:**
 - Load data values from memory into registers.
 - Process data in registers using a number of data processing instructions which are not slowed down by memory access.
 - Store results from registers out to memory.
- * **The ARM has three sets of instructions which interact with main memory. These are:**
 - Single register data transfer (LDR / STR).
 - Block data transfer (LDM/STM).
 - Single Data Swap (SWP).

Single register data transfer

- * **The basic load and store instructions are:**
 - Load and Store Word or Byte
 - LDR / STR / LDRB / STRB
- * **ARM Architecture Version 4 also adds support for halfwords and signed data.**
 - Load and Store Halfword
 - LDRH / STRH
 - Load Signed Byte or Halfword - load value and sign extend it to 32 bits.
 - LDRSB / LDRSH
- * **All of these instructions can be conditionally executed by inserting the appropriate condition code after STR / LDR.**
 - e.g. LDREQB
- * **Syntax:**
 - $\langle \text{LDR|STR} \rangle \{ \langle \text{cond} \rangle \} \{ \langle \text{size} \rangle \} \text{Rd}, \langle \text{address} \rangle$


Single register data transfer



Load and Store Word or Byte: Base Register

* **The memory location to be accessed is held in a base register**

- `STR r0, [r1]` ; Store contents of r0 to location pointed to
; by contents of r1.
- `LDR r2, [r1]` ; Load r2 with contents of memory location
; pointed to by contents of r1.




Load and Store Word or Byte: Offsets from the Base Register

- * As well as accessing the actual location contained in the base register, these instructions can access a location offset from the base register pointer.
- * This offset can be
 - An unsigned 12bit immediate value (ie 0 - 4095 bytes).
 - A register, optionally shifted by an immediate value
- * This can be either added or subtracted from the base register:
 - Prefix the offset value or register with '+' (default) or '-'.
- * This offset can be applied:
 - before the transfer is made: *Pre-indexed addressing*
 - optionally *auto-incrementing* the base register, by postfixing the instruction with an '!'.
 - after the transfer is made: *Post-indexed addressing*
 - causing the base register to be *auto-incremented*.

Load and Store Word or Byte: Pre-indexed Addressing


* **Example:** STR r0, [r1,#12]



- * **To store to location `0x1f4` instead use:** STR r0, [r1,#-12]
- * **To auto-increment base pointer to `0x20c` use:** STR r0, [r1, #12]!
- * **If r2 contains 3, access `0x20c` by multiplying this by 4:**
 - STR r0, [r1, r2, LSL #2]

Load and Store Word or Byte: Post-indexed Addressing

* **Example:** STR r0, [r1], #12



* To auto-increment the base register to location `0x1f4` instead use:

- `STR r0, [r1], #-12`

* If `r2` contains 3, auto-increment base register to `0x20c` by multiplying this by 4:

- `STR r0, [r1], r2, LSL #2`

Load and Stores with User Mode Privilege

- * **When using post-indexed addressing, there is a further form of Load/Store Word/Byte:**
 - $\langle \text{LDR|STR} \rangle \{ \langle \text{cond} \rangle \} \{ \text{B} \} \text{T Rd}, \langle \text{post_indexed_address} \rangle$
- * **When used in a privileged mode, this does the load/store with user mode privilege.**
 - Normally used by an exception handler that is emulating a memory access instruction that would normally execute in user mode.

Example Usage of Addressing Modes

* Imagine an array, the first element of which is pointed to by the contents of r0.


* If we want to access a particular element, then we can use pre-indexed addressing:

- r1 is element we want.
- LDR r2, [r0, r1, LSL #2]

* If we want to step through every element of the array, for instance to produce sum of elements in the array, then we can use post-indexed addressing within a loop:


- r1 is address of current element (initially equal to r0).
- LDR r2, [r1], #4

Use a further register to store the address of final element, so that the loop can be correctly terminated.



Quiz #4

- * Write a segment of code that add together elements x to $x+(n-1)$ of an array, where the element $x=0$ is the first element of the array.
- * Each element of the array is word sized (ie. 32 bits).
- * The segment should use post-indexed addressing.
- * At the start of your segments, you should assume that:
 - $r0$ points to the start of the array.
 - $r1 = x$
 - $r2 = n$




Quiz #4 - Sample Solution

```
__ADD r0, r0, r1, LSL#2      ; Set r0 to address of element x
  ADD r2, r0, r2, LSL#2      ; Set r2 to address of element n+1
  MOV r1, #0                 ; Initialise counter
loop
  LDR r3, [r0], #4           ; Access element and move to next
  ADD r1, r1, r3             ; Add contents to counter
  CMP r0, r2                 ; Have we reached element x+n?
  BLT loop                   ; If not - repeat for
                              ;       next element
                              ; on exit sum contained in r1
```

Block Data Transfer (1)

- * **The Load and Store Multiple instructions (LDM / STM) allow between 1 and 16 registers to be transferred to or from memory.**
- * **The transferred registers can be either:**
 - Any subset of the current bank of registers (default).
 - Any subset of the user mode bank of registers when in a privileged mode (postfix instruction with a '^').




Block Data Transfer (2)

- * **Base register used to determine where memory access should occur.**
 - 4 different addressing modes allow increment and decrement inclusive or exclusive of the base register location.
 - Base register can be optionally updated following the transfer (by appending it with an '!').
 - Lowest register number is always transferred to/from lowest memory location accessed.
- * **These instructions are very efficient for**
 - Saving and restoring context
 - For this useful to view memory as a stack.
 - Moving large blocks of data around memory
 - For this useful to directly represent functionality of the instructions.

Stacks


- * A stack is an area of memory which grows as new data is “pushed” onto the “top” of it, and shrinks as data is “popped” off the top.
- * Two pointers define the current limits of the stack.
 - A base pointer
 - used to point to the “bottom” of the stack (the first location).
 - A stack pointer
 - used to point the current “top” of the stack.



Stack Operation

- * **Traditionally, a stack grows down in memory, with the last “pushed” value at the lowest address. The ARM also supports ascending stacks, where the stack structure grows up through memory.**
- * **The value of the stack pointer can either:**
 - Point to the last occupied address (Full stack)
 - and so needs pre-decrementing (ie before the push)
 - Point to the next occupied address (Empty stack)
 - and so needs post-decrementing (ie after the push)
- * **The stack type to be used is given by the postfix to the instruction:**
 - STMFD / LDMFD : Full Descending stack
 - STMFA / LDMFA : Full Ascending stack.
 - STMED / LDMED : Empty Descending stack
 - STMEA / LDMEA : Empty Ascending stack
- * **Note: ARM Compiler will always use a Full descending stack.**

Stack Examples



Stacks and Subroutines

- * **One use of stacks is to create temporary register workspace for subroutines. Any registers that are needed can be pushed onto the stack at the start of the subroutine and popped off again at the end so as to restore them before return to the caller :**

```
STMFD sp!, {r0-r12, lr}      ; stack all registers
.....                       ; and the return address
.....
LDMFD sp!, {r0-r12, pc}      ; load all the registers
                              ; and return automatically
```

- * **See the chapter on the ARM Procedure Call Standard in the SDT Reference Manual for further details of register usage within subroutines.**
- * **If the pop instruction also had the ‘S’ bit set (using ‘^’) then the transfer of the PC when in a privileged mode would also cause the SPSR to be copied into the CPSR (see exception handling module).**


Direct functionality of Block Data Transfer

- * **When LDM / STM are not being used to implement stacks, it is clearer to specify exactly what functionality of the instruction is:**
 - i.e. specify whether to increment / decrement the base pointer, before or after the memory access.
- * **In order to do this, LDM / STM support a further syntax in addition to the stack one:**
 - STMIA / LDMIA : Increment After
 - STMIB / LDMIB : Increment Before
 - STMDA / LDMDA : Decrement After
 - STMDB / LDMDB : Decrement Before

Example: Block Copy

- Copy a block of memory, which is an exact multiple of 12 words long from the location pointed to by r12 to the location pointed to by r13. r14 points to the end of block to be copied.

```
; r12 points to the start of the source data
; r14 points to the end of the source data
; r13 points to the start of the destination data
loop    LDMIA    r12!, {r0-r11} ; load 48 bytes
        STMIA    r13!, {r0-r11} ; and store them
        CMP      r12, r14       ; check for the end
        BNE      loop          ; and loop until done
```




- This loop transfers 48 bytes in 31 cycles
- Over 50 Mbytes/sec at 33 MHz

Quiz #5


- * **The contents of registers r0 to r6 need to be swapped around thus:**
 - r0 moved into r3
 - r1 moved into r4
 - r2 moved into r6
 - r3 moved into r5
 - r4 moved into r0
 - r5 moved into r1
 - r6 moved into r2
- * **Write a segment of code that uses full descending stack operations to carry this out, and hence requires no use of any other registers for temporary storage.**

Quiz #5 - Sample Solution




Swap and Swap Byte Instructions

- * **Atomic operation of a memory read followed by a memory write which moves byte or word quantities between registers and memory.**
- * **Syntax:**
 - `SWP{<cond>}{B} Rd, Rm, [Rn]`



- * **Thus to implement an actual swap of contents make $Rd = Rm$.**
- * **The compiler cannot produce this instruction.**

Software Interrupt (SWI)



- * In effect, a SWI is a user-defined instruction.
- * It causes an exception trap to the SWI hardware vector (thus causing a change to supervisor mode, plus the associated state saving), thus causing the SWI exception handler to be called.
- * The handler can then examine the comment field of the instruction to decide what operation has been requested.
- * By making use of the SWI mechanism, an operating system can implement a set of privileged operations which applications running in user mode can request.
- * See Exception Handling Module for further details.

PSR Transfer Instructions

- * **MRS and MSR allow contents of CPSR/SPSR to be transferred from appropriate status register to a general purpose register.**

- All of status register, or just the flags, can be transferred.

- * **Syntax:**

- `MRS{<cond>} Rd, <psr>` ; `Rd = <psr>`
- `MSR{<cond>} <psr>, Rm` ; `<psr> = Rm`
- `MSR{<cond>} <psrf>, Rm` ; `<psrf> = Rm`

where


- `<psr>` = CPSR, CPSR_all, SPSR or SPSR_all
- `<psrf>` = CPSR_flg or SPSR_flg

- * **Also an immediate form**

- `MSR{<cond>} <psrf>, #Immediate`
- This immediate must be a 32-bit immediate, of which the 4 most significant bits are written to the flag bits.

Using MRS and MSR

- * **Currently reserved bits, may be used in future, therefore:**
 - they must be preserved when altering PSR
 - the value they return must not be relied upon when testing other bits.




- * **Thus read-modify-write strategy must be followed when modifying any PSR:**
 - Transfer PSR to register using MRS
 - Modify relevant bits
 - Transfer updated value back to PSR using MSR
- * **Note:**
 - In User Mode, all bits can be read but only the flag bits can be written to.

Quiz #6

* **Write a short code segment that performs a mode change by modifying the contents of the CPSR**

- The mode you should change to is user mode which has the value 0x10.
- This assumes that the current mode is a privileged mode such as supervisor mode.
- This would happen for instance when the processor is reset - reset code would be run in supervisor mode which would then need to switch to user mode before calling the main routine in your application.
- You will need to use MSR and MRS, plus 2 logical operations.



Quiz #6 - Sample Solution

*** Set up useful constants:**

```
mmask  EQU    0x1f           ; mask to clear mode bits
userm   EQU    0x10          ; user mode value
```

*** Start off here in supervisor mode.**

```
    MRS    r0, cpsr           ; take a copy of the CPSR
    BIC    r0, r0, #mmask     ; clear the mode bits
    ORR    r0, r0, #userm     ; select new mode
    MSR    cpsr, r0           ; write back the modified
                                ; CPSR
```

*** End up here in user mode.**

Main features of the ARM Instruction Set

- * **All instructions are 32 bits long.**
- * **Most instructions execute in a single cycle.**
- * **Every instruction can be conditionally executed.**
- * **A load/store architecture**
 - Data processing instructions act only on registers
 - Three operand format
 - Combined ALU and shifter for high speed bit manipulation
 - Specific memory access instructions with powerful auto-indexing addressing modes.
 - 32 bit and 8 bit data types
 - ▣ and also 16 bit data types on ARM Architecture v4.
 - Flexible multiple register load and store instructions
- * **Instruction set extension via coprocessors**

Thumb Instruction Set

- * **16 bits.**
- * **Without conditional execution.**
- * **Simpler than the 16-bit counterpart.**
- * **A Thumb instruction is expanded into its ARM instruction counterpart by hardware.**
- * **Instruction execution just like an ARM instruction.**

Thumb Instruction Set Format

	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
1	0	0	0	Op		Offset5					Rs		Rd			Move shifted register	
2	0	0	0	1	1	I	Op	Rn/offset3			Rs		Rd			Add/subtract	
3	0	0	1	Op		Rd			Offset8								Move/compare/add /subtract immediate
4	0	1	0	0	0	0	Op			Rs		Rd			ALU operations		
5	0	1	0	0	0	1	Op		H1	H2	Rs/Hs		Rd/Hd			Hi register operations /branch exchange	
6	0	1	0	0	1	Rd			Word8								PC-relative load
7	0	1	0	1	L	B	0	Ro			Rb		Rd			Load/store with register offset	
8	0	1	0	1	H	S	1	Ro			Rb		Rd			Load/store sign-extended byte/halfword	
9	0	1	1	B	L	Offset5					Rb		Rd			Load/store with immediate offset	
10	1	0	0	0	L	Offset5					Rb		Rd			Load/store halfword	
11	1	0	0	1	L	Rd			Word8								SP-relative load/store
12	1	0	1	0	SP	Rd			Word8								Load address
13	1	0	1	1	0	0	0	0	S	SWord7							Add offset to stack pointer
14	1	0	1	1	L	1	0	R	Rlist								Push/pop registers
15	1	1	0	0	L	Rb			Rlist								Multiple load/store
16	1	1	0	1	Cond					Soffset8							Conditional branch
17	1	1	0	1	1	1	1	1	Value8								Software Interrupt
18	1	1	1	0	0	Offset11											Unconditional branch
19	1	1	1	1	H	Offset											Long branch with link
	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	